

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

EnviroSense2 (E2) Environmental Sensor Module with Temperature and Digital Outputs

MODEL NUMBER: E2MTDO











Monitors ambient temperature conditions and enables remote control of peripherals, including beacons and alarm signals.

Description

The E2MTDO E2 Environmental Sensor Module works with Tripp Lite LX Platform devices, including WEBCARDLX, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs. By connecting the included USB cable to an LX Platform device, the E2MTDO allows you to remotely monitor ambient temperature conditions in network environments. It also allows you to remotely turn on and off two compatible products, such as beacons and alarm signals.

If temperature values exceed a certain limit or the digital output changes state, it is recorded in the event log of the LX Platform device's PowerAlert® Device Manager interface. The E2MTDO mounts magnetically to most racks and cabinets. Up to three E2 modules can be daisy-chained together. A built-in retention harness secures cable connections to reduce clutter.

Features

Compatible with Tripp Lite LX Platform Devices

- Compatible devices include WEBCARDLX, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs
- Measures and monitors ambient temperature
- Enables remote control of peripherals, such as beacons and alarm signals
- Supports both AC- and DC-powered peripherals

Easy to Install and Operate

- Attaches magnetically to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together

Highlights

- Compatible with Tripp Lite LX Platform devices
- Easy magnetic mounting to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together
- Built-in cable harness reduces clutter
- USB cable included

Package Includes

- E2MTDO EnviroSense2
 Environmental Sensor Module
- USB cable (A/Micro-B), 3 ft.
- · Owner's manual



- Built-in cable harness reduces clutter
- USB cable included
- Compatible with Tripp Lite's free downloadable PowerAlert software

Specifications

OVERVIEW	
UPC Code	037332196279
INPUT	
Cable Length (ft.)	3
PHYSICAL	
Shipping Dimensions (hwd / cm)	2.79 x 11.18 x 15.24
Shipping Dimensions (hwd / in.)	1.10 x 4.40 x 6.00
Shipping Weight (kg)	0.13
Shipping Weight (lbs.)	0.29
CONNECTIONS	
Side A - Connector 1	USB A (FEMALE)
Side B - Connector 1	MICRO-USB B (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies